

## TBC 600-2 kanaals

TBC 612-2-15    TBC 612-2-25    TBC 612-2-35    TBC 624-2-10    TBC 624-2-20    TBC 624-2-30

Ingangsspanning <i>Input Voltage</i>	230VAC 115VAC	180 - 240VAC, 50/60Hz 95 - 125VAC, 50/60Hz					
Uitgangsspanning (nominaal) <i>Output voltage (nominal)</i>		12VDC			24VDC		
Inschakelspanning <i>Active battery Voltage</i>		$\geq 4$ Volts			$\geq 7$ Volts		
Laadspanningen <i>Charge voltages</i>		14,4 / 13,5 Vdc			28,8 Vdc / 27 Vdc		
Laadkarakteristiek <i>Charge curve</i>		IUoUoe					
Max. laadstroom <i>Maximum charge current</i>		15 Amp.	25 Amp.	35 Amp.	10 Amp.	20 Amp.	30 Amp.
Max. dynamostroom <i>Max. dynamo current</i>		150 Amp.			80 Amp.		
Max. lichtnetbelasting <i>Max. lighting load</i>	230VAC 115VAC	1,8 Amp.	2,6 Amp.	3,8 Amp.	2,5 Amp.	4,4 Amp.	6,6 Amp.
		3,7 Amp.	6,1 Amp.	8,3 Amp.	5,3 Amp.	10 Amp.	14,5 Amp.
Ideale omgevingstemperatuur <i>Ideal working temperature</i>		5-20°C					
Beveiligingen <i>Protections</i>		Ompoling, kortsluiting (uitgang), temperatuur, ingangsspanning, stroombegrenzing <i>Reverse polarisation, short circuit, temperature, inputvoltage, current limitation</i>					
Max. luchtvochtigheid <i>Max. relative humidity</i>		90%					
Koeling <i>Ventilation</i>		Convectie <i>Convection</i>					
Batterij aansluiting <i>Battery connection</i>		M6 bouten (messing nikkel) <i>M6 bolts (brass nickel)</i>					
Soft start <i>Soft start</i>		Primair en secundair <i>Primary and secondary</i>					
Galvanisch gescheiden <i>Galvanic separated</i>		Ja <i>Yes</i>					
Behuizing <i>Housing</i>		Aluminium <i>Aluminium</i>					
Beschermingsgraad (EMC) <i>Level of protection (EMC)</i>		IP 647					
Afmetingen (lxbxh in cm) <i>Dimensions (lxwxh cm)</i>		25x20x11	30x20x11	25x20x11	30x20x11		
Gewicht (kg) <i>Weight (kg)</i>		8	10	8	10		

